

**B.PRO**  
CATERING SOLUTIONS



# B.PROTHERM K

**Good on the go. Synthetic food transport containers.**

# APPETIZER

**Food on the go: Quality equipment for the most demanding requirements.**

If you take pleasure in good food, you enjoy dining at a restaurant with an excellent kitchen. For first-class distribution of great quality food, you would select a **B.PROTHERM**. You will be delighted with the complete successful product range with all the details that are required to suit the **perfect food transportation**.

The **B.PROTHERM K system family** is available in five different sizes, with a variety of extras and transport aids, unheated, heatable and **with convection heating**. All models are extremely attractive, with their **5-star quality** technology, design, material, function and accessories. B.PROTHERM offers absolute top quality at a fair price.

As a special “treat”, we’d like to introduce you to

the **adjustable B.PROTHERM. Degree-precise temperature adjustment** and an LED display allow you to adapt the unit to each individual food item.

**B.PROTHERM serves quality you can taste.**



**BPT 620 KBRUH (with accessories)**

Front loader with convection heating adjustable to the degree (max. 85 °C) and overheating protection against undesired subsequent cooking.

## CONTENTS

|                                |    |
|--------------------------------|----|
| The B.PROTHERM K system family | 4  |
| Every feature is a delicacy    | 5  |
| Temperature adjustment         |    |
| Down to the degree             | 6  |
| B.PROTHERM K, heatable         | 8  |
| B.PROTHERM K, unheated         | 10 |

## PRODUCT OVERVIEW

|                                       |    |
|---------------------------------------|----|
| B.PROTHERM K, unheated                | 12 |
| B.PROTHERM K, with silicone heating   | 16 |
| B.PROTHERM K, with convection heating | 17 |
| Accessories for B.PROTHERM K          | 20 |
| <b>Loading examples</b>               | 23 |



# A SPECIAL TREAT

**Everything just falls into place: The B.PROTHERM K system family.**

From exclusive private events to large-scale functions, from top-notch hotels to distribution in canteens and hospitals, kindergartens and dining halls – with B.PROTHERM K you're always excellently equipped:

- Top loader, front loader, unheated, heatable, adjustable, and all this in five sizes.
- All products work hand in hand, are compatible and have a wide range of uses.

## **Well thought-out details simplify food transport and storage:**

- The B.PROTHERM K models are made of deep-drawn synthetic. They are especially easy to carry, extremely rugged and look great too.

- The double-walled synthetic body and the clever insulation of CFC-free PUR foam **reliably maintain the temperature** for many hours (also see page 10).
- Skids fixed to the bottom of the containers ensure a **secure grip** at all times, even with space-saving stacking.

With B.PROTHERM, you're prepared for just about anything. As an added bonus, the units can always be upgraded.

## **Have a good time catering!**



## **Unmistakeable: B.PROTHERM K with your logo or company name**

- For B.PROTHERM K models
- Available for just 1 unit or more
- Customised text, such as company name or logo, to your specifications
- Perfectly legible, high-quality laser marking
- Permanent and dishwasher-safe

## Every feature a delicacy.



### Outstanding food quality

Heatable B.PROTHERM with interior temperature adjustable down to the degree from +40 °C to +85 °C or +95 °C. A B.PRO innovation.



### Sturdy and easy to carry

Rugged stainless-steel clamps with non-slip synthetic handles durably stand up to even the toughest strains.



### For direct loading

Hygienic, practical, simply good: B.PROTHERM 320 KB and KBR can even be loaded without GN containers thanks to the stainless-steel inlet.



### Perfect division

The recessed areas for crossbars enable loading with smaller GN containers.



### Off to the dishwasher

For the sake of hygiene: All B.PROTHERM K are completely dishwasher-safe. Heatable models BPT 320: with sealable power connection socket. Convection heated models BPT 420 and 620: without door.



### Environmentally friendly

B.PROTHERM Ks made of environmentally friendly polypropylene are CFC-free and recyclable, non-hazardous and food-resistant.



### Add more colour to your life:

#### B.PROTHERM K with coloured fastening components.

In addition to the familiar dark grey, all B.PROTHERM synthetic models are now also available with blue, red, green and yellow fastening components. Naturally, your logo or customised text can also be applied on all new colours.



### The perfect addition:

#### B.PROTHERM E made of stainless steel.

B.PROTHERM E offers you new transport containers made of stainless steel – in three different sizes, unheated, with convection heating or with convection cooling. All models are compatible with B.PROTHERM K made of synthetic. We'll be happy to send you additional information (see back for address).

# SPOT-ON TEMPERATURES

**My food is ideal** down to the exact degree: **B.PROTHERM K** with individually adjustable interior temperature.



**With the adjustable models from B.PROTHERM K, you specify the temperature:**

Now even the most sensitive foods can be kept warm gently thanks to the interior temperature adjustable to the degree – preventing excessive subsequent cooking and drying out.

**Fish stays tender, broccoli stays firm and sausages don't burst.**

**B.PROTHERM K models with adjustable interior temperature:**

Top loader with silicone heating, can also be used as a bain-marie

- B.PROTHERM 320 KBR

Front loaders with convection heating

- B.PROTHERM 420 KBRUH
- B.PROTHERM 620 KBRUH
- B.PROTHERM 620 KBRUH-F (with and without condensation water trough)



**B.PROTHERM 320 KBR (with accessories)**

Top loader with silicone heating adjustable to the degree (max. 95 °C) and stainless-steel inlay for direct loading or as a bain-marie.

## A hot innovation from B.PRO Catering Solutions – the adjustable interior temperature for outstanding food quality:

- **Free choice of temperatures**

Setting and adjustment of the temperature to the degree from +40 °C to +85 °C/+95 °C.

- **Full monitoring**

The LED display indicates the temperature inside the container.

- **Overheating protection**

All heatable B.PROTHERMs are equipped with an electronic temperature limitation against undesired subsequent cooking.

- **Serving exactly to the degree**

Food at precisely the right temperature thanks to exact adjustment of the temperature from +40 °C to +85 °C/+95 °C.

- **Low-temperature cooking exactly to the degree**

The adjustable heater ensures tender meat enjoyment in the temperature range from +60 °C to +80 °C – over night as well to save energy (B.PROTHERM 420 KBRUH and 620 KBRUH).

- **Sous-Vide cooking exactly to the degree**

Simply cook the vacuum-packed fresh food in a water bath between +55 °C and +85 °C. This especially preserves vitamins and nutrients and ensures genuine, natural flavours (B.PROTHERM 320 KBR).



## All B.PROTHERM K models at a glance.

| overview of B.PROTHERM K (synthetic) | unheated                                                                             | heatable                                                              | heat- and adjustable with temperature display                            |
|--------------------------------------|--------------------------------------------------------------------------------------|-----------------------------------------------------------------------|--------------------------------------------------------------------------|
| Front loader = loaded from the front | BPT 420 K<br>BPT 620 KUF<br>BPT 620 KUF-F<br>BPT 620 KUS<br>BPT 620 KF<br>BPT 620 KV | Convection heating:<br>BPT 420 KBUH<br>BPT 620 KBUH<br>BPT 620 KBUH-F | Convection heating:<br>BPT 420 KBRUH<br>BPT 620 KBRUH<br>BPT 620 KBRUH-F |
| Top loader = loaded from above       | BPT 160 K<br>BPT 320 K<br>BPT 320 ECO<br>BPT 320 ECO-C                               | Silicone heating:<br>BPT 320 KB                                       | Silicone heating:<br>BPT 320 KBR                                         |

### Model designations

|       |                                                       |
|-------|-------------------------------------------------------|
| BPT   | = B.PROTHERM                                          |
| K     | = synthetic                                           |
| KB    | = synthetic, heatable                                 |
| KBR   | = synthetic, heatable, adjustable                     |
| KBUH  | = synthetic, heatable, convection heating             |
| KBRUH | = synthetic, heatable, adjustable, convection heating |
| KF    | = synthetic, mobile                                   |
| KUF   | = synthetic, unheated, hinged door                    |
| KUS   | = synthetic, unheated, snap-on lid                    |
| KV    | = synthetic, lock at top                              |
| -F    | = mobile                                              |
| -C    | = catering                                            |

# MASTERCLASS

## Warmly recommended: B.PROTHERM K front loaders with convection heating.

The **convection-heated** light-weight boxes made of synthetic are available in two sizes, each **with or without temperature control**. All eight models are front loaders; the heating module is integrated in the hinged door.

B.PROTHERM K with convection heating offers you advantages that you would not find elsewhere:

- **Outstanding food quality**

An electronic controller prevents the temperature in the interior from climbing above +90 °C – even on models without temperature control. This prevents undesired subsequent cooking or even drying out of the food thus preserving vitamins and nutrients.

- **Uniform temperature distribution**

The integrated convection heating ensures a uniform temperature distribution in the interior.

### B.PROTHERM K models with convection heating (front loaders):

Heatable with convection heating

- B.PROTHERM 420 KBUH
- B.PROTHERM 620 KBUH
- B.PROTHERM 620 KBUH-F (with and without condensation water trough)

Heatable and adjustable with convection heating

- B.PROTHERM 420 KBRUH
- B.PROTHERM 620 KBRUH
- B.PROTHERM 620 KBRUH-F (with and without condensation water trough)



**BPT 420 KBUH (with accessories).** All B.PROTHERM Ks with convection heating are equipped with electronic overheating protection against undesired subsequent cooking.



#### Hygienic, practical, simply good

The air at the top is drawn in directly through a labyrinth. The entry of dirt and trickling of sauces into the fan is prevented due to this being shielded by a cover.



#### Hot air for hot food

The specialised air-discharge opening ensures especially even air distribution inside the container. This keeps even larger quantities of food almost completely evenly heated.



#### Safety first

Safety for the unit and the user: The safety door can only be removed in a predefined position, i.e. unintentional removal is prevented.

## Much more than just transporting: B.PROTHERM K top loaders with silicone heating.

With the two 320 KB models, B.PROTHERM presents innovative top loaders with silicone heating.

Thanks to the integrated stainless-steel inlet, the B.PROTHERM 320 KB **can be loaded directly** or used as a **bain-marie**.

A great idea from B.PRO Catering Solutions that's also appetising for gourmets. Even very sensitive food can be kept hot gently.

### • Food at the perfect temperature

The high-quality stainless-steel inlet ensures optimum heat transmission from the reliable silicone heater.

### • Off to the dishwasher

The B.PROTHERM 320 KB models are also dishwasher-safe even without removing the heating system (with sealable power connection socket). It doesn't get any better than this.

### B.PROTHERM K models with silicone heating (top loaders):

Heatable with silicone heating

- B.PROTHERM 320 KB

Heatable and adjustable with silicone heating

- B.PROTHERM 320 KBR



**BPT 320 KB (with accessories).** Thanks to their integrated stainless-steel inlet, B.PROTHERM Ks with silicone heating can be directly loaded with food – without extra Gastronorm containers.



### Easy to use

Even models without temperature control indicate in a flash whether the B.PROTHERM is connected to the power supply thanks to the operating mode indicator.



Also available with temperature control exactly to the degree!

# GOURMET

**Whether cold or hot – stays tasty for hours:**

**Unheated B.PROTHERM K for any application.**

On all B.PROTHERM you can depend on the first-class insulating properties. Even the unheated models shine with excellent values.

**This will keep the food appetisingly fresh, even after hours of containment.**

With warm food, the temperature drops no more than 1.5 °C an hour (in accordance with DIN EN 12571, exception: BPT 160 K, 320 ECO, 320 ECO-C).

With cold food, the temperature rises no more than 0.5 °C an hour (in accordance with DIN EN 12571, exception: BPT 160 K, 320 ECO, 320 ECO-C).

For longer-lasting transport or storage periods, the eutectic plate (accessory, page 21) also ensures optimum cooling.




**B.PROTHERM 620 KUF** (with accessories)  
unheated, with eutectic plate at top for extra-long cooling, hinged door can be swivelled by 270° and removed.



**B.PROTHERM 620 KV** (with accessories)  
unheated, with removable door


## Better than the standard requires: the insulation of the B.PROTHERM K

(Example BPT 620, all tested models are shown on pages 12 to 15)



### Cool-down curve (with hot foods):

According to DIN EN 12571 (grey line), the temperature of food filled while hot (75 °C) may not drop below 65 °C within three hours. With the BPT 620 (blue line), the food is still a tasty 73.1 °C hot after three hours (checking under normal conditions; the values may differ in practice depending on the working and ambient conditions).



### Warm-up curve (with cold foods):

To fulfil the DIN EN 12571 standard (grey line), the temperature of cold filled food (3 °C) may rise to a maximum of 7 °C within three hours. With the BPT 620 (blue line), the food is still 3.75 °C cold after three hours (checking under normal conditions; the values may differ in practice depending on the working and ambient conditions).



#### **B.PROTHERM 320 ECO**

The basic model: unheated **with a lid that sits securely (not clamped)**, easy to open



#### **Cleverly insulated**

The double-walled body and the insulation of CFC-free PUR foam ensure even-temperature food transport.




#### **Easy to remove**

The trick with the click on the B.PROTHERM 620 KV: the food can easily be removed with the lock at the top – even if the containers are stacked tightly next to one another.

## **The B.PROTHERM ECO-C for smooth transport logistics when catering: High capacity with maximum flexibility**



**Safe access.** The cut-outs in the B.PROTHERM 320 ECO-C simplify stacking and removing of GN containers and provide fingers with space for grasping safely.



**Can be loaded in stacks.** For maximum capacity, the GN containers can be stacked next to and on top of each other in various heights and sizes in the B.PROTHERM 320 ECO-C.

#### **B.PROTHERM 320 ECO-C**

For maximum flexibility when providing decentralised supply with various menu components.

## B.PROTHERM K, UNHEATED

The table with loading examples is located on page 23.

We will be happy to provide you with additional information on these products and on the entire B.PRO product line on request (see back for address).



| Model                                                                                                                                  | BPT 320 ECO                                                                     | BPT 320 ECO-C                                                                                                                  | BPT 160 K<br>Shown with accessory                                                                                 | BPT 320 K                                                                              |
|----------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| Designation                                                                                                                            | B.PROTHERM 320 ECO                                                              | B.PROTHERM 320 ECO-C                                                                                                           | B.PROTHERM 160 K                                                                                                  | B.PROTHERM 320 K                                                                       |
| Model                                                                                                                                  | Unheated,<br>top loader                                                         |                                                                                                                                |                                                                                                                   |                                                                                        |
| Dimensions L x W x H                                                                                                                   | 630 x 415 x 345 mm                                                              | 630 x 415 x 345 mm                                                                                                             | 634 x 430 x 230 mm                                                                                                | 643 x 430 x 340 mm                                                                     |
| Capacity                                                                                                                               | GN 1/1-200<br>or its subdivisions                                               | 4x GN 1/1-55*<br>3x GN 1/1-65*<br>2x GN 1/1-100*<br>1x GN 1/1-200*<br>*or its subdivisions                                     | GN 1/1-100<br>or its subdivisions                                                                                 | GN 1/1-200<br>or its subdivisions                                                      |
| Weight                                                                                                                                 | 7.0 kg                                                                          | 7.0 kg                                                                                                                         | 7.0 kg                                                                                                            | 8.0 kg                                                                                 |
| Lock/lid                                                                                                                               | Lid sits securely<br>(not clamped),<br>easy to open and close                   |                                                                                                                                | Locked via stainless-steel bent-clamp closures in the short<br>sides of the container which engage in the lid     |                                                                                        |
| Container inner space                                                                                                                  | Depressions near the edge<br>for secure acceptance of<br>intermediate crossbars | With handle openings in the<br>edge area for simple removal<br>of the GN containers                                            | Depressions near the edge for secure acceptance of intermedi-<br>ate crossbars                                    |                                                                                        |
| Special features                                                                                                                       | Moulded skids                                                                   |                                                                                                                                | Ergonomically shaped stainless-steel carrying hoops with syn-<br>thetic carrying handles, attached to short sides |                                                                                        |
|                                                                                                                                        |                                                                                 | Especially large interior for<br>stacking GN containers of dif-<br>ferent sizes and depths next<br>to and on top of each other |                                                                                                                   |                                                                                        |
| Cool-down curve<br>according to<br>DIN EN 12571<br>(Temperature of hot food<br>after three hours,<br>for explanations, see<br>page 10) |                                                                                 |                                                                                                                                |                                                                                                                   |                                                                                        |
| Warm-up curve<br>according to<br>DIN EN 12571<br>(Temperature of cold<br>food after three hours,<br>for explanations, see<br>page 10)  |                                                                                 |                                                                                                                                |                                                                                                                   |                                                                                        |
| Material                                                                                                                               | Polypropylene, polyamide                                                        | Polypropylene, polyamide                                                                                                       | Polypropylene, polyamide, stainless steel                                                                         |                                                                                        |
| Order No. *grey<br>blue<br>red<br>green<br>yellow                                                                                      | <b>564 650</b>                                                                  | <b>573 956</b>                                                                                                                 | <b>566 240</b><br><b>574 526</b><br><b>574 527</b><br><b>574 528</b><br><b>574 529</b>                            | <b>566 241</b><br><b>574 530</b><br><b>574 531</b><br><b>574 532</b><br><b>574 533</b> |

\* Colour of fastening components



| BPT 420 K                                                                                                                                                                                                                                                                                                                                                                                                                                                                | BPT 620 KUS<br>Shown with accessory GN containers                                                             | BPT 620 KV<br>Shown with accessory GN containers                                                                    |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|---------------------|----|------|------|----|------|------|----|------|------|-----|------|------|-----|------|------|-----|------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------------|---------------------|----|------|------|----|------|------|----|------|------|-----|------|------|-----|------|------|-----|------|------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|------------------|---------------------|----|------|------|----|------|------|----|------|------|-----|------|------|-----|------|------|-----|------|------|
| B.PROTHERM 420 K                                                                                                                                                                                                                                                                                                                                                                                                                                                         | B.PROTHERM 620 KUS                                                                                            | B.PROTHERM 620 KV                                                                                                   |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Unheated,<br>front loader with hinged door                                                                                                                                                                                                                                                                                                                                                                                                                               | Unheated,<br>front loader with removable door                                                                 | Unheated,<br>front loader with removable door, lock at top                                                          |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 663 x 445 x 470 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 630 x 430 x 660 mm                                                                                            | 630 x 430 x 660 mm                                                                                                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 2x GN 1/1-150<br>or their subdivisions                                                                                                                                                                                                                                                                                                                                                                                                                                   | 2x GN 1/1-200 or<br>3x GN 1/1-150<br>or their subdivisions                                                    | 2x GN 1/1-200 or<br>3x GN 1/1-150<br>or their subdivisions                                                          |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 12.0 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 15.0 kg                                                                                                       | 14.0 kg                                                                                                             |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Locked via stainless-steel bent-clamp closure in the long side of the container,<br>which engages in the door                                                                                                                                                                                                                                                                                                                                                            |                                                                                                               | Lock at top                                                                                                         |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Hinged door can be swivelled by 270°<br>and removed                                                                                                                                                                                                                                                                                                                                                                                                                      | Removable door                                                                                                |                                                                                                                     |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 11 pairs of moulded support ledges with a distance of 31 mm between ledges for the insertion of GN containers                                                                                                                                                                                                                                                                                                                                                            | 12 pairs of moulded support ledges with a distance of 39 mm between ledges for the insertion of GN containers |                                                                                                                     |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides                                                                                                                                                                                                                                                                                                                                                              |                                                                                                               |                                                                                                                     |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Gripping depression at upper left in the door for easy handling                                                                                                                                                                                                                                                                                                                                                                                                          | --                                                                                                            | Lock at top, removable door – allows stacked or neighbouring containers to be emptied easily even if space is tight |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| <div>Temp. of hot food in °C</div> <div><table><thead><tr><th>Time in minutes</th><th>BLT 420 K: 70,5°</th><th>DIN EN 12571: 65,0°</th></tr></thead><tbody><tr><td>30</td><td>70.5</td><td>65.0</td></tr><tr><td>60</td><td>69.5</td><td>64.5</td></tr><tr><td>90</td><td>68.5</td><td>64.0</td></tr><tr><td>120</td><td>67.5</td><td>63.5</td></tr><tr><td>150</td><td>66.5</td><td>63.0</td></tr><tr><td>180</td><td>65.5</td><td>62.5</td></tr></tbody></table></div> | Time in minutes                                                                                               | BLT 420 K: 70,5°                                                                                                    | DIN EN 12571: 65,0° | 30 | 70.5 | 65.0 | 60 | 69.5 | 64.5 | 90 | 68.5 | 64.0 | 120 | 67.5 | 63.5 | 150 | 66.5 | 63.0 | 180 | 65.5 | 62.5 | <div>Temp. of hot food in °C</div> <div><table><thead><tr><th>Time in minutes</th><th>BLT 620 K: 66,2°</th><th>DIN EN 12571: 65,0°</th></tr></thead><tbody><tr><td>30</td><td>66.2</td><td>65.0</td></tr><tr><td>60</td><td>65.5</td><td>64.5</td></tr><tr><td>90</td><td>64.8</td><td>64.0</td></tr><tr><td>120</td><td>64.1</td><td>63.5</td></tr><tr><td>150</td><td>63.4</td><td>63.0</td></tr><tr><td>180</td><td>62.7</td><td>62.5</td></tr></tbody></table></div> | Time in minutes | BLT 620 K: 66,2° | DIN EN 12571: 65,0° | 30 | 66.2 | 65.0 | 60 | 65.5 | 64.5 | 90 | 64.8 | 64.0 | 120 | 64.1 | 63.5 | 150 | 63.4 | 63.0 | 180 | 62.7 | 62.5 | <div>Temp. of hot food in °C</div> <div><table><thead><tr><th>Time in minutes</th><th>BLT 620 K: 66,2°</th><th>DIN EN 12571: 65,0°</th></tr></thead><tbody><tr><td>30</td><td>66.2</td><td>65.0</td></tr><tr><td>60</td><td>65.5</td><td>64.5</td></tr><tr><td>90</td><td>64.8</td><td>64.0</td></tr><tr><td>120</td><td>64.1</td><td>63.5</td></tr><tr><td>150</td><td>63.4</td><td>63.0</td></tr><tr><td>180</td><td>62.7</td><td>62.5</td></tr></tbody></table></div> | Time in minutes | BLT 620 K: 66,2° | DIN EN 12571: 65,0° | 30 | 66.2 | 65.0 | 60 | 65.5 | 64.5 | 90 | 64.8 | 64.0 | 120 | 64.1 | 63.5 | 150 | 63.4 | 63.0 | 180 | 62.7 | 62.5 |
| Time in minutes                                                                                                                                                                                                                                                                                                                                                                                                                                                          | BLT 420 K: 70,5°                                                                                              | DIN EN 12571: 65,0°                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 30                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 70.5                                                                                                          | 65.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 69.5                                                                                                          | 64.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 90                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 68.5                                                                                                          | 64.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 67.5                                                                                                          | 63.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 66.5                                                                                                          | 63.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 180                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 65.5                                                                                                          | 62.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Time in minutes                                                                                                                                                                                                                                                                                                                                                                                                                                                          | BLT 620 K: 66,2°                                                                                              | DIN EN 12571: 65,0°                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 30                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 66.2                                                                                                          | 65.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 65.5                                                                                                          | 64.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 90                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 64.8                                                                                                          | 64.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 64.1                                                                                                          | 63.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 63.4                                                                                                          | 63.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 180                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 62.7                                                                                                          | 62.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Time in minutes                                                                                                                                                                                                                                                                                                                                                                                                                                                          | BLT 620 K: 66,2°                                                                                              | DIN EN 12571: 65,0°                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 30                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 66.2                                                                                                          | 65.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 65.5                                                                                                          | 64.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 90                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 64.8                                                                                                          | 64.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 64.1                                                                                                          | 63.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 63.4                                                                                                          | 63.0                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 180                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 62.7                                                                                                          | 62.5                                                                                                                |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| <div>Temp. of cold food in °C</div> <div><table><thead><tr><th>Time in minutes</th><th>BLT 420 K: 4,85°</th><th>DIN EN 12571: 7,0°</th></tr></thead><tbody><tr><td>30</td><td>4.85</td><td>7.0</td></tr><tr><td>60</td><td>5.0</td><td>7.2</td></tr><tr><td>90</td><td>5.1</td><td>7.4</td></tr><tr><td>120</td><td>5.2</td><td>7.6</td></tr><tr><td>150</td><td>5.3</td><td>7.8</td></tr><tr><td>180</td><td>5.4</td><td>8.0</td></tr></tbody></table></div>            | Time in minutes                                                                                               | BLT 420 K: 4,85°                                                                                                    | DIN EN 12571: 7,0°  | 30 | 4.85 | 7.0  | 60 | 5.0  | 7.2  | 90 | 5.1  | 7.4  | 120 | 5.2  | 7.6  | 150 | 5.3  | 7.8  | 180 | 5.4  | 8.0  | <div>Temp. of cold food in °C</div> <div><table><thead><tr><th>Time in minutes</th><th>BLT 620 K: 3,75°</th><th>DIN EN 12571: 7,0°</th></tr></thead><tbody><tr><td>30</td><td>3.75</td><td>7.0</td></tr><tr><td>60</td><td>3.8</td><td>7.2</td></tr><tr><td>90</td><td>3.85</td><td>7.4</td></tr><tr><td>120</td><td>3.9</td><td>7.6</td></tr><tr><td>150</td><td>3.95</td><td>7.8</td></tr><tr><td>180</td><td>4.0</td><td>8.0</td></tr></tbody></table></div>          | Time in minutes | BLT 620 K: 3,75° | DIN EN 12571: 7,0°  | 30 | 3.75 | 7.0  | 60 | 3.8  | 7.2  | 90 | 3.85 | 7.4  | 120 | 3.9  | 7.6  | 150 | 3.95 | 7.8  | 180 | 4.0  | 8.0  | <div>Temp. of cold food in °C</div> <div><table><thead><tr><th>Time in minutes</th><th>BLT 620 K: 3,75°</th><th>DIN EN 12571: 7,0°</th></tr></thead><tbody><tr><td>30</td><td>3.75</td><td>7.0</td></tr><tr><td>60</td><td>3.8</td><td>7.2</td></tr><tr><td>90</td><td>3.85</td><td>7.4</td></tr><tr><td>120</td><td>3.9</td><td>7.6</td></tr><tr><td>150</td><td>3.95</td><td>7.8</td></tr><tr><td>180</td><td>4.0</td><td>8.0</td></tr></tbody></table></div>          | Time in minutes | BLT 620 K: 3,75° | DIN EN 12571: 7,0°  | 30 | 3.75 | 7.0  | 60 | 3.8  | 7.2  | 90 | 3.85 | 7.4  | 120 | 3.9  | 7.6  | 150 | 3.95 | 7.8  | 180 | 4.0  | 8.0  |
| Time in minutes                                                                                                                                                                                                                                                                                                                                                                                                                                                          | BLT 420 K: 4,85°                                                                                              | DIN EN 12571: 7,0°                                                                                                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 30                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 4.85                                                                                                          | 7.0                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 5.0                                                                                                           | 7.2                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 90                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 5.1                                                                                                           | 7.4                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 5.2                                                                                                           | 7.6                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 5.3                                                                                                           | 7.8                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 180                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 5.4                                                                                                           | 8.0                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Time in minutes                                                                                                                                                                                                                                                                                                                                                                                                                                                          | BLT 620 K: 3,75°                                                                                              | DIN EN 12571: 7,0°                                                                                                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 30                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.75                                                                                                          | 7.0                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.8                                                                                                           | 7.2                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 90                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.85                                                                                                          | 7.4                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3.9                                                                                                           | 7.6                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3.95                                                                                                          | 7.8                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 180                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4.0                                                                                                           | 8.0                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Time in minutes                                                                                                                                                                                                                                                                                                                                                                                                                                                          | BLT 620 K: 3,75°                                                                                              | DIN EN 12571: 7,0°                                                                                                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 30                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.75                                                                                                          | 7.0                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 60                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.8                                                                                                           | 7.2                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 90                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.85                                                                                                          | 7.4                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 120                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3.9                                                                                                           | 7.6                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 150                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 3.95                                                                                                          | 7.8                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| 180                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | 4.0                                                                                                           | 8.0                                                                                                                 |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| Polypropylene, polyamide, stainless steel                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                                                               |                                                                                                                     |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |
| <b>573 514</b><br><b>574 534</b><br><b>574 535</b><br><b>574 536</b><br><b>574 537</b>                                                                                                                                                                                                                                                                                                                                                                                   | <b>566 243</b><br><b>574 538</b><br><b>574 539</b><br><b>574 540</b><br><b>574 541</b>                        | <b>564 358</b>                                                                                                      |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                 |                  |                     |    |      |      |    |      |      |    |      |      |     |      |      |     |      |      |     |      |      |







## B.PROTHERM K, **UNHEATED**



| Model                                                                                                                | BPT 620 KUF<br>Shown with accessory GN containers                                                                                                                                                | BPT 620 KUF-F                                                                          |
|----------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------|
| Designation                                                                                                          | B.PROTHERM 620 KUF                                                                                                                                                                               | B.PROTHERM 620 KUF-F                                                                   |
| Model                                                                                                                | Unheated,<br>front loader with hinged door                                                                                                                                                       | Unheated,<br>front loader with hinged door,<br>mobile                                  |
| Dimensions L x W x H                                                                                                 | 660 x 440 x 660 mm                                                                                                                                                                               | 710 x 440 x 831 mm                                                                     |
| Capacity                                                                                                             | 2x GN 1/1-200 or<br>3x GN 1/1-150 or their subdivisions                                                                                                                                          |                                                                                        |
| Weight                                                                                                               | 15.5 kg                                                                                                                                                                                          | 25.0 kg                                                                                |
| Lock/lid                                                                                                             | - Locked via stainless-steel bent-clamp closure in the long side of the container, which engages in the door<br>- Hinged door can be swivelled by 270° and removed                               |                                                                                        |
| Container inner space                                                                                                | - 12 pairs of moulded support ledges with a distance of 39 mm between ledges for the insertion of GN containers                                                                                  |                                                                                        |
| Special features                                                                                                     | - Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides<br>- Gripping depression on the short side in the door for easy handling<br><br>-- |                                                                                        |
| Cool-down curve according to DIN EN 12571 (Temperature of hot food after three hours, for explanations, see page 10) | Temp. of hot food in °C<br>BLT 160 K: 66,2°<br>DIN EN 12571: 65,0°                                                                                                                               | Temp. of hot food in °C<br>BLT 160 K: 66,2°<br>DIN EN 12571: 65,0°                     |
| Warm-up curve according to DIN EN 12571 (Temperature of cold food after three hours, for explanations, see page 10)  | Temp. of cold food in °C<br>DIN EN 12571: 7,0°<br>BLT 620 K: 3,75°                                                                                                                               | Temp. of cold food in °C<br>DIN EN 12571: 7,0°<br>BLT 620 K: 3,75°                     |
| Material                                                                                                             | Polypropylene, polyamide,<br>stainless steel                                                                                                                                                     |                                                                                        |
| Order No. *grey<br>blue<br>red<br>green<br>yellow                                                                    | <b>564 365</b><br><b>574 542</b><br><b>574 543</b><br><b>574 544</b><br><b>574 545</b>                                                                                                           | <b>569 262</b><br><b>574 546</b><br><b>574 547</b><br><b>574 548</b><br><b>574 549</b> |

\* Colour of fastening components



| BPT 620 KUF-F<br>with condensation water trough                                                                               | BPT 620 KF                                                                                                      | BPT 620 KF<br>with condensation water trough                                                                      |
|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| B.PROTHERM 620 KUF-F with condensation water trough                                                                           | B.PROTHERM 620 KF                                                                                               | B.PROTHERM 620 KF with condensation water trough                                                                  |
| Unheated,<br>front loader with hinged door,<br>mobile                                                                         | Unheated,<br>front loader with removable door,<br>mobile                                                        | Unheated,<br>front loader with removable door,<br>mobile                                                          |
| 747 x 440 x 831 mm                                                                                                            | 680 x 430 x 831 mm                                                                                              | 747 x 430 x 831 mm                                                                                                |
| 2x GN 1/1-200 or<br>3x GN 1/1-150 or their subdivisions                                                                       |                                                                                                                 |                                                                                                                   |
| 25.7 kg                                                                                                                       | 27.0 kg                                                                                                         | 24.7 kg                                                                                                           |
| - Locked via stainless-steel bent-clamp closure in the long side of the container, which engages in the door                  |                                                                                                                 |                                                                                                                   |
| - Hinged door can be swivelled by 270° and removed                                                                            | - Removable door                                                                                                |                                                                                                                   |
| - 12 pairs of moulded support ledges with a distance of 39 mm between ledges for the insertion of GN containers               |                                                                                                                 |                                                                                                                   |
| - Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides                 |                                                                                                                 |                                                                                                                   |
| - Mobile (4 steering castors, 2 of which have brakes, corrosion-resistant according to DIN 18867-8)                           |                                                                                                                 |                                                                                                                   |
| - With collecting channel for condensation water<br><br>- Gripping depression on the short side in the door for easy handling | --                                                                                                              | - With collecting channel for condensation water                                                                  |
| Temp. of hot food in °C<br>                | Temp. of hot food in °C<br>  | Temp. of hot food in °C<br>  |
| Temp. of cold food in °C<br>               | Temp. of cold food in °C<br> | Temp. of cold food in °C<br> |
| Polypropylene, polyamide,<br>stainless steel                                                                                  |                                                                                                                 |                                                                                                                   |
| 573 317<br>574 550<br>574 551<br>574 552<br>574 553                                                                           | 564 350<br>574 554<br>574 555<br>574 556<br>574 557                                                             | 573 316<br>574 558<br>574 559<br>574 560<br>574 561                                                               |

## B.PROTHERM K, HEATABLE/HEATABLE AND ADJUSTABLE (TOP LOADER WITH SILICONE HEATING)

The table with loading examples is located on page 23.

We will be happy to provide you with additional information on these products and on the entire B.PRO product line on request (see back for address).



| Model                                             | BPT 320 KB<br>Shown with accessory GN containers                                                                                                                                                                                                                                                                                   | BPT 320 KBR<br>Shown with accessory GN containers                                                                                   |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Designation                                       | B.PROTHERM 320 KB                                                                                                                                                                                                                                                                                                                  | B.PROTHERM 320 KBR                                                                                                                  |
| Model                                             | Heatable, top loader                                                                                                                                                                                                                                                                                                               | Heatable, adjustable, with temperature indicator, top loader                                                                        |
| Dimensions L x W x H                              | 643 x 430 x 375 mm                                                                                                                                                                                                                                                                                                                 |                                                                                                                                     |
| Capacity                                          | GN 1/1-200 or its subdivisions                                                                                                                                                                                                                                                                                                     |                                                                                                                                     |
| Weight                                            | 13.5 kg                                                                                                                                                                                                                                                                                                                            |                                                                                                                                     |
| Connected load                                    | 220–240 V (AC)/50–60 Hz/400 W                                                                                                                                                                                                                                                                                                      |                                                                                                                                     |
| Heating/<br>Temperature range                     | - Energy-saving silicone heating<br>- Electrical connection via power plug coupling (found on short side) which can be closed water-tight via the special rotary lock<br>- Operation indication via LED                                                                                                                            |                                                                                                                                     |
|                                                   |                                                                                                                                                                                                                                                                                                                                    | - Temperature inside the container is adjustable down to the degree from +40 °C to +95 °C                                           |
| Lock/lid                                          | - Locked via stainless-steel bent-clamp closures in the short sides of the container which engage in the lid                                                                                                                                                                                                                       |                                                                                                                                     |
| Container inner space                             | - Depressions near the edge for secure acceptance of intermediate crossbars                                                                                                                                                                                                                                                        |                                                                                                                                     |
| Special features                                  | - Cleanable in a dishwasher at up to +90 °C thanks to the sealable power conn. socket<br>- Stainless-steel interior container enables direct loading<br>- Heatable wet or dry (heat loss occurs with dry heating)<br>- Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides |                                                                                                                                     |
|                                                   | --                                                                                                                                                                                                                                                                                                                                 | - Temperature adjustment down to the degree from +40 °C to +95 °C via digital regulator<br>- Temperature indication via LED display |
| Material                                          | Polypropylene, polyamide, stainless steel                                                                                                                                                                                                                                                                                          |                                                                                                                                     |
| Protection type                                   | IP X6                                                                                                                                                                                                                                                                                                                              |                                                                                                                                     |
| Order No. *grey<br>blue<br>red<br>green<br>yellow | <b>566 242</b><br><b>574 563</b><br><b>574 564</b><br><b>574 565</b><br><b>574 566</b>                                                                                                                                                                                                                                             | <b>572 228</b><br><b>574 567</b><br><b>574 568</b><br><b>574 569</b><br><b>574 570</b>                                              |

## B.PROTHERM K, **HEATABLE/HEATABLE AND ADJUSTABLE** (FRONT LOADER WITH CONVECTION HEATING)



| Model                                             | BPT 420 KBUH                                                                                                                                                                                                                                                                                                                                                                                                                                   | BPT 420 KBRUH                                                                                                                                                                                                                                                                                  |
|---------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Designation                                       | B.PROTHERM 420 KBUH                                                                                                                                                                                                                                                                                                                                                                                                                            | B.PROTHERM 420 KBRUH                                                                                                                                                                                                                                                                           |
| Model                                             | Heatable, front loader                                                                                                                                                                                                                                                                                                                                                                                                                         | Heatable, adjustable, with temperature indicator, front loader                                                                                                                                                                                                                                 |
| Dimensions L x W x H                              | 692 x 445 x 470 mm                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                |
| Capacity                                          | 2x GN 1/1-150                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                                                                                                                                                                                                                                |
| Weight                                            | 16.0 kg                                                                                                                                                                                                                                                                                                                                                                                                                                        |                                                                                                                                                                                                                                                                                                |
| Connected load **                                 | 220–240 V AC/50–60 Hz/200 W                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                                                                                                                                                                                                |
| Heating/temperature range                         | <ul style="list-style-type: none"> <li>- Convection heating module</li> <li>- Electrical connection via power plug coupling which can be closed water-tight via the special rotary lock</li> <li>- “Power” operating mode indicator</li> <li>- Electronic temperature limitation of max. +90 °C</li> </ul>                                                                                                                                     |                                                                                                                                                                                                                                                                                                |
| Lock/lid                                          | <ul style="list-style-type: none"> <li>- Locked via stainless-steel bent-clamp closure on the long side of the container, which securely fastens the door</li> <li>- Hinged door can be swivelled by 270° and removed</li> </ul>                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                                |
| Container inner space                             | - 11 pairs of moulded support ledges with a distance of 31 mm between ledges for the insertion of GN containers                                                                                                                                                                                                                                                                                                                                |                                                                                                                                                                                                                                                                                                |
| Special features                                  | <ul style="list-style-type: none"> <li>- Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides</li> <li>- Gripping depression situated to the upper left of the door for easier movement and improved handling of the container</li> <li>- Without door, dishwasher-safe up to a maximum of +90 °C</li> <li>- Gripping depression at upper left in the door for easy handling</li> </ul> |                                                                                                                                                                                                                                                                                                |
|                                                   | --                                                                                                                                                                                                                                                                                                                                                                                                                                             | <ul style="list-style-type: none"> <li>- Temperature inside the container is adjustable down to the degree from +40 °C to +85 °C</li> <li>- Temperature adjustment down to the degree from +40 °C to +85 °C via digital regulator</li> <li>- Temperature indication via LED display</li> </ul> |
| Material                                          | Polypropylene, polyamide, stainless steel                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                                                                                                                                                                                |
| Protection type                                   | IP X4                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                                                                                                                                                                                                |
| Order No. *grey<br>blue<br>red<br>green<br>yellow | <b>573 515</b><br><b>574 571</b><br><b>574 572</b><br><b>574 573</b><br><b>574 574</b>                                                                                                                                                                                                                                                                                                                                                         | <b>573 516</b><br><b>574 575</b><br><b>574 576</b><br><b>574 577</b><br><b>574 578</b>                                                                                                                                                                                                         |

\*\* The workplace-specific noise level of the unit is less than 70 dB(A).

## B.PROTHERM K, **HEATABLE** (FRONT LOADER WITH CONVECTION HEATING)



| Model                                             | BPT 620 KBUH<br>Shown with accessory GN containers                                                                                                                                                                                                                                                            | BPT 620 KBUH-F                                                                                      | BPT 620 KBUH-F<br>with condensation water trough                                                                                                        |
|---------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------|
| Designation                                       | B.PROTHERM 620 KBUH                                                                                                                                                                                                                                                                                           | B.PROTHERM 620 KBUH-F                                                                               | B.PROTHERM 620 KBUH-F<br>with condensation water trough                                                                                                 |
| Model                                             | Heatable,<br>front loader                                                                                                                                                                                                                                                                                     | Heatable,<br>front loader, mobile                                                                   |                                                                                                                                                         |
| Dimensions L x W x H                              | 692 x 440 x 660 mm                                                                                                                                                                                                                                                                                            | 742 x 440 x 831 mm                                                                                  | 747 x 440 x 831 mm                                                                                                                                      |
| Capacity                                          | 2x GN 1/1-200 or<br>3x GN 1/1-150 or their subdivisions                                                                                                                                                                                                                                                       |                                                                                                     |                                                                                                                                                         |
| Weight                                            | 19.5 kg                                                                                                                                                                                                                                                                                                       | 27.0 kg                                                                                             | 28.0 kg                                                                                                                                                 |
| Connected load **                                 | 220-240 V AC/50-60 Hz/200 W                                                                                                                                                                                                                                                                                   |                                                                                                     |                                                                                                                                                         |
| Heating/<br>temperature range                     | <ul style="list-style-type: none"> <li>- Convection heating module</li> <li>- electrical connection via power plug coupling which can be closed water-tight via the special rotary lock</li> <li>- "Power" operating mode indicator</li> <li>- Electronic temperature limitation of max. +90 °C</li> </ul>    |                                                                                                     |                                                                                                                                                         |
| Lock/lid                                          | - Locked via stainless-steel bent-clamp closure in the long side of the container, which engages in the door                                                                                                                                                                                                  |                                                                                                     |                                                                                                                                                         |
| Container<br>inner space                          | - 12 pairs of moulded support ledges with a distance of 39 mm between ledges for the insertion of GN containers                                                                                                                                                                                               |                                                                                                     |                                                                                                                                                         |
| Special features                                  | <ul style="list-style-type: none"> <li>- Without door, dishwasher-safe up to a maximum of +90 °C</li> <li>- Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides</li> <li>- Gripping depression at upper left in the door for easy handling</li> </ul> |                                                                                                     |                                                                                                                                                         |
|                                                   | --                                                                                                                                                                                                                                                                                                            | - Mobile (4 steering castors, 2 of which have brakes, corrosion-resistant according to DIN 18867-8) | - Mobile (4 steering castors, 2 of which have brakes, corrosion-resistant according to DIN 18867-8)<br>- With collecting channel for condensation water |
| Material                                          | Polypropylene, polyamide, stainless steel                                                                                                                                                                                                                                                                     |                                                                                                     |                                                                                                                                                         |
| Protection type                                   | IP X4                                                                                                                                                                                                                                                                                                         |                                                                                                     |                                                                                                                                                         |
| Order No. *grey<br>blue<br>red<br>green<br>yellow | <b>572 536</b><br><b>574 579</b><br><b>574 580</b><br><b>574 581</b><br><b>574 582</b>                                                                                                                                                                                                                        | <b>573 314</b><br><b>574 583</b><br><b>574 584</b><br><b>574 585</b><br><b>574 586</b>              | <b>573 318</b><br><b>574 587</b><br><b>574 588</b><br><b>574 589</b><br><b>574 590</b>                                                                  |


## B.PROTHERM K, **HEATABLE AND ADJUSTABLE** (FRONT LOADER WITH CONVECTION HEATING)



| BPT 620 KBRUH                                                                                                                                                                                                                                                                                                                                                                                                                                                    | BPT 620 KBRUH-F                                                                                            | BPT 620 KBRUH-F<br>with condensation water trough                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| B.PROTHERM 620 KBRUH                                                                                                                                                                                                                                                                                                                                                                                                                                             | B.PROTHERM 620 KBRUH-F                                                                                     | B.PROTHERM 620 KBRUH-F<br>with condensation water trough                                                                                                       |
| Heatable,<br>adjustable, with temperature indicator,<br>front loader                                                                                                                                                                                                                                                                                                                                                                                             | Heatable,<br>adjustable, with temperature indicator,<br>front loader, mobile                               |                                                                                                                                                                |
| 692 x 440 x 660 mm                                                                                                                                                                                                                                                                                                                                                                                                                                               | 742 x 440 x 831 mm                                                                                         | 747 x 440 x 831 mm                                                                                                                                             |
| 2x GN 1/1-200 or<br>3x GN 1/1-150 or their subdivisions                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                            |                                                                                                                                                                |
| 19.5 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                          | 27.0 kg                                                                                                    | 28.0 kg                                                                                                                                                        |
| 220-240 V AC/50-60 Hz/200 W                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                            |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>- Convection heating module</li> <li>- Temperature inside the container is adjustable down to the degree from +40 °C to +85 °C</li> <li>- Electrical connection via power plug coupling which can be closed water-tight via the special rotary lock</li> </ul>                                                                                                                                                            |                                                                                                            |                                                                                                                                                                |
| - Locked via stainless-steel bent-clamp closure in the long side of the container, which engages in the door                                                                                                                                                                                                                                                                                                                                                     |                                                                                                            |                                                                                                                                                                |
| - 12 pairs of moulded support ledges with a distance of 39 mm between ledges for the insertion of GN containers                                                                                                                                                                                                                                                                                                                                                  |                                                                                                            |                                                                                                                                                                |
| <ul style="list-style-type: none"> <li>- Without door, dishwasher-safe up to a maximum of +90 °C</li> <li>- Ergonomically shaped stainless-steel carrying hoops with synthetic carrying handles, attached to long sides</li> <li>- Temperature adjustment down to the degree from +40 °C to +85 °C via digital regulator</li> <li>- Temperature indication via LED display</li> <li>- Gripping depression at upper left in the door for easy handling</li> </ul> |                                                                                                            |                                                                                                                                                                |
| --                                                                                                                                                                                                                                                                                                                                                                                                                                                               | - Mobile (4 steering castors, 2 of<br>which have brakes, corrosion-<br>resistant according to DIN 18867-8) | - Mobile (4 steering castors, 2 of<br>which have brakes, corrosion-<br>resistant according to DIN 18867-8)<br>- With collecting channel for condensation water |
| Polypropylene, polyamide,<br>stainless steel                                                                                                                                                                                                                                                                                                                                                                                                                     |                                                                                                            |                                                                                                                                                                |
| IP X4                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                                                            |                                                                                                                                                                |
| <b>572 537</b><br><b>574 591</b><br><b>574 592</b><br><b>574 593</b><br><b>574 594</b>                                                                                                                                                                                                                                                                                                                                                                           | <b>573 315</b><br><b>574 595</b><br><b>574 596</b><br><b>574 597</b><br><b>574 598</b>                     | <b>573 319</b><br><b>574 599</b><br><b>574 600</b><br><b>574 601</b><br><b>574 602</b>                                                                         |

## ACCESSORIES

| Illustration                                                                                     | Model Designation                                      | for models                                                                                                       | Dimensions<br>L x W x H<br>(in mm) | Weight<br>(kg)                            | Castors<br>125 mm dia.                                                                                                             | Order No.                            |
|--------------------------------------------------------------------------------------------------|--------------------------------------------------------|------------------------------------------------------------------------------------------------------------------|------------------------------------|-------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------|
|                 | <b>ROLA 13</b><br>Serving dolly<br>with lid receptacle | 1 x BPT 160 K<br>or<br>1 x BPT 320 ECO/K/KB/KBR                                                                  | 592 x 425 x 535                    | 10.0<br><br>Load-bearing<br>cap.<br>50 kg | 4 steering castors,<br>2 of which have<br>brakes<br>Synthetic,<br>corrosion-resist.<br>acc. to DIN 18867-<br>8<br>Galvanised steel | <b>572 341</b><br><br><b>572 342</b> |
|                | <b>ROLLI-100</b><br>Transport dolly                    | 4 x BPT 160 K or<br>3 x BPT 320 ECO/K/KB/KBR<br>or<br>2 x BPT 420 K/KBUH/KBRUH<br>or<br>2 x BPT 620 K/KBUH/KBRUH | 643 x 446 x 159                    | 4.5<br><br>Load-bearing<br>cap.<br>130 kg | 4 steering castors,<br>2 of which have<br>brakes,<br>100 mm dia.<br>Galvanised steel                                               | <b>568 236</b>                       |
|               | <b>ROLLI-125</b><br>Transport dolly                    | 4 x BPT 160 K<br>or<br>3 x 320 ECO/K/KB/KBR<br>or<br>2 x BPT 420 K/KBUH/KBRUH<br>or<br>2 x BPT 620 K/KBUH/KBRUH  | 643 x 446 x 187                    | 4.5<br><br>Load-bearing<br>cap.<br>180 kg | 4 steering castors,<br>2 of which have<br>brakes<br>Synthetic,<br>corrosion-resist.<br>acc. to DIN 18867-<br>8                     | <b>568 237</b>                       |
| not shown<br> | <b>Push bar</b><br>for better<br>manoeuvring           | ROLLI-100<br>or<br>ROLLI-125                                                                                     | 800<br>Ø 20                        | --                                        | --                                                                                                                                 | <b>568 926</b>                       |

| Illustration                                                                        | Model Designation                                                                                                                     | for models                                                                                                          | Dimensions<br>L x W x H<br>(in mm)                                                                 | Weight<br>(kg)                                                           | Castors<br>125 mm dia.                                                                                             | Order No.                            |
|-------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|--------------------------------------|
|    | <b>BTA 3</b><br>Transport and serving trolley                                                                                         | 2 x BPT 160 K<br>or<br>2 x BPT 320 ECO/K/KB/KBR<br>or<br>2 x BPT 420 K/KBUH/KBRUH<br>or<br>2 x BPT 620 K/KBUH/KBRUH | 1070 x 780 x 840<br><br>Shelf dimensions:<br>940 x 700<br><br>Clear height between shelves:<br>300 | 31.0<br>Load-bearing cap.<br>150 kg<br><br>Max. load per shelf<br>100 kg | 4 steering castors, 2 of which have brakes<br>Synthetic, corrosion-resist. acc. to DIN 18867-8<br>Galvanised steel | <b>572 325</b><br><br><b>572 326</b> |
|  | <b>Eutectic plate</b><br>(-3 °C), sythentic, Gastronorm-compatible                                                                    | BPT 420 K or BPT 620 K<br><br>BPT 160 K or BPT 320 ECO/K                                                            | 530 x 325 x 30<br><br>483 x 283 x 36                                                               | 4.2<br><br>4.0                                                           |                                | <b>568 136</b><br><br><b>569 315</b> |
|                                                                                     | <b>Eutectic plate</b><br>(-12 °C), sythentic, Gastronorm-compatible                                                                   | BPT 420 K or BPT 620 K                                                                                              | 530 x 325 x 30                                                                                     | 4.2                                                                      | --                                                                                                                 | <b>573 332</b>                       |
|  | <b>Slide-in frame</b><br>made of stainless steel for Gastronorm containers, suitable up to 150 mm depth                               | BPT 420 K/KBUH/KBRUH<br>or<br>BPT 620 K/KBUH/KBRUH                                                                  | 530 x 325 x 156                                                                                    | 0.50                                                                     | --                                                                                                                 | <b>564 352</b>                       |
|  | <b>ST 3</b><br>GN support bar made of stainless steel for container combination, required with GN 1/4, 1/6 and 1/9                    | BPT 160 K<br>or<br>BPT 320 ECO/K/KB/KBR<br>or<br>slide-in frame                                                     | Length: 325 mm                                                                                     | --                                                                       | --                                                                                                                 | <b>550 650</b>                       |
|  | <b>ST 5</b><br>GN support bar made of stainless steel, with spring lock, for container combination, required with GN 1/4, 1/6 and 1/9 | BPT 160 K<br>or<br>BPT 320 ECO/K/KB/KBR<br>or<br>slide-in frame                                                     | Length: 530 mm                                                                                     | --                                                                       | --                                                                                                                 | <b>550 651</b>                       |

## ACCESSORIES

| Illustration                                                                      | Model Designation                                                                  | for models | Dimensions<br>L x W x H<br>(in mm) | Weight<br>(kg) | Castors<br>125 mm dia. | Order No.      |
|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------|------------------------------------|----------------|------------------------|----------------|
|  | <b>Special pen</b><br>Special washable pen for writing on the menu cards           | all BPT K  | --                                 | --             | --                     | <b>564 361</b> |
|  | <b>B.PROTHERM menu card</b><br>blank                                               | all BPT K  | DIN A6<br>(148 x 105 mm)           | --             | --                     | <b>564 353</b> |
|  | <b>Menu card box</b><br>Card box for B.PROTHERM menu cards<br>(Capacity: 25 cards) | all BPT K  | --                                 | --             | --                     | <b>564 355</b> |

## OPTIONS

| Illustration                                                                        | Model Designation                                                                                                                                    | For models                                                    | Colour        |
|-------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------|
|  | <b>Coloured fastening components</b>                                                                                                                 | All BPT Ks<br>(except BPT 320 ECO, BPT 320 ECO-C, BPT 620 KV) | <b>grey</b>   |
|                                                                                     |                                                                                                                                                      |                                                               | <b>blue</b>   |
|                                                                                     |                                                                                                                                                      |                                                               | <b>red</b>    |
|                                                                                     |                                                                                                                                                      |                                                               | <b>green</b>  |
|                                                                                     |                                                                                                                                                      |                                                               | <b>yellow</b> |
|  | <b>Customer logo</b><br>Laser-engraved<br>Engraved on the handle carrier flaps on both sides;<br>can be imprinted on all fastening component colours | All BPT Ks<br>(except BPT 320 ECO, BPT 320 ECO-C)             |               |

## LOADING EXAMPLES

### Loading examples for B.PROTHERM 160 K, B.PROTHERM 320 K





For a  
3-component meal:  
2 x GN 1/4 100 mm deep  
1 x GN 1/2 100 mm deep  
1 support ST 3  
(approx. 14 meals)




For a  
4-component meal:  
2 x GN 1/6 100 mm deep  
2 x GN 1/3 100 mm deep  
2 supports ST 3  
(approx. 10 meals)

### Loading examples for B.PROTHERM 420 K

For a  
3-component meal:  
1 x GN 1/1-65,  
2 x GN 1/1-100  
(approx. 40 meals)




11 x GN 1/1-20



1 x GN 1/1-20,  
5 x GN 1/1-40





2 x GN 1/1-20,  
3 x GN 1/1-65



2 x GN 1/1-150

For a  
4-component meal:  
2 x GN 1/1-40,  
2 x GN 1/1-65  
(approx. 30 meals)



1 cooling element,  
10 x GN 1/1-20



1 x GN 1/1-20,  
2 x GN 1/1-40,  
2 x GN 1/1-65





1 x GN 1/1-20,  
1 x GN 1/1-40,  
2 x GN 1/1-100




1 x GN 1/1-40,  
1 x GN 1/1-200

### Loading examples for B.PROTHERM 620 K


For a  
3-component meal:  
1 x GN 1/1-65,  
1 x GN 1/1-100,  
1 x GN 1/1-200  
(approx. 60 meals)




12 x GN 1/1-20



2 x GN 1/1-20,  
5 x GN 1/1-65





6 x GN 1/1-65




4 x GN 1/1-100

For a  
4-component meal:  
2 x GN 1/1-65,  
2 x GN 1/1-100  
(approx. 40 meals)




3 x GN 1/1-150




1 x GN 1/1-20,  
2 x GN 1/1-200




1 cooling element,  
11 x GN 1/1-20



1 x GN 1/1-40,  
5 x GN 1/1-65




1 x GN 1/1-20,  
1 x GN 1/1-40,  
3 x GN 1/1-100



2 x GN 1/1-40,  
2 x GN 1/1-150



3 x GN 1/1-40,  
2 x GN 1/1-65



1 x GN 1/1-100,  
1 x GN 1/1-150,  
1 x GN 1/1-200

## THE B.PRO GROUP

Our customers are as diverse and varied as our portfolio. To ensure we do our very best for every client, we concentrate our skills, abilities and capacities in two highly specialised business units: B.PRO Catering Solutions – Products and systems for professional commercial kitchens. ENOXX Engineering – Custom-made high-precision pieces using stainless steel, aluminium or synthetics for industry.

All business units of B.PRO hold DIN EN ISO9001:2015 certification, guaranteeing a high standard of reliability and customer orientation.

B.PRO GmbH  
B.PRO Catering Solutions  
P.O. Box 13 10  
75033 Oberderdingen  
Germany  
Phone +49 7045 44-81900  
[catering.export@bpro-solutions.com](mailto:catering.export@bpro-solutions.com)  
[www.bpro-solutions.com](http://www.bpro-solutions.com)

**B.PRO**  
CATERING SOLUTIONS